



CLW07

LED Corn Bulb

Project: _____ Type: _____

Name: _____ Date: _____

18W



54W



Size	18W: 5.7" x 2.6" x 2.6" 54W: 9.5" x 3.4" x 3.4"	Lumens	18W: 2430-2610lm 54W: 5670-6750lm
Watts	18W, 54W	CCT	3000K, 5700K
Voltage	AC100-277V	IP Rating	IP64
Dimming	Non-Dimming	Materials	Aluminum, PC
Beam Angle	360°	Finish	White
CRI	>80	Lens	Clear
PF	≥0.9	Lifespan	50,000 Hours

OVERVIEW

- Applications:** Outdoor IP64
- Efficacy:** 135-145lm/W
- Dimming:** Non-Dimming
- LED Type:** SMD2835
- Lens Type:** Clear
- Lifespan:** 50,000 Hours

FEATURES

- 18W version uses E26 Base Socket
- 54W version uses E39 Base Socket
- Built-in Heat Sink & Vent
- Energy-Efficient, Ultra Bright LEDs
- High-Efficiency Aluminum Heat-Dispersing





SARIN LED CORN BULBS are commonly used to replace HID lamps and metal halide bulbs. These lamps offer high-efficiency lighting without sacrificing light intensity. The aluminum housing, built-in heat sink and ventilation all provide the optimal heat-dispersal methods available for this type of lighting.

Corn bulbs require water-tight casing if they are going to be used for outdoor application but are rated at a phenomenal IP rating of 64. Corn bulbs are ideal for lamp posts, gas stations, hospitals, and office buildings. The two wattages have differing socket sizes to meet fixture requirements.





PHOTOMETRICS:

18W



54W





CLW07

LED Corn Bulb

Project: _____ Type: _____

Name: _____ Date: _____

ORDER FORM:

(*) Special Order/Not Commonly Stocked

Custom Model Assembly

Fixture	CCT	Watts	Beam Angle	Voltage
<input checked="" type="checkbox"/> CLW07	<input type="checkbox"/> 3000K	<input type="checkbox"/> 18W	<input checked="" type="checkbox"/> 360°	<input checked="" type="checkbox"/> 100-277
	<input type="checkbox"/> 5700K	<input type="checkbox"/> 54W		

SES-CLW07E-3000-18
Example Model Number

SES - CLW07 - 360 - 100-277

Quantity

Fixture

CCT

Watts

Beam Angle

Voltage

Common Stock Models:

Item #	Model #
10044	SES-CLW07E-3000-18
10045	SES-CLW07E-5700-18
10046	SES-CLW07E-5700-54E39

DIMENSIONS:

