

DL4 & SINGLE CCT DL6 DISC LIGHT

Ρ	roi	е	с	t	:	

Name:

Type:_

Date:___



Watts	DL4: 10W	DL6: 15W		
ССТ	3000K, 5000K		, 4000K, 00K	
Size	5.9" L x 5.9" W x 0.9 7.2" L x 7.2" W x 0.9		Lumens	DL4: 800lm DL6: 1,100lm
Voltage	120V		IP Rating	IP44
Dimming	TRIAC		Materials	Aluminum, PC
Beam Angle	120°		Finish	White
CRI	>90		Lens	Clear
PF	≥ 0.9		Lifespan	50,000 Hours

SARIN LED Single CCT Disc Lights are commonly used in spaces with high ceilings like hotels, living spaces, schools, and offices. These ceiling lights are safe for indoor use. It can be installed virtually anywhere, provides true color rendering with 90+ CRI, and can be continuously dimmed to 10% with standard dimmers.

Extremely easy to install, this powerful recessed Disc Light is equipped with a quick-connect case and conduit to integrate with an existing fixture frame junction box.



OVERVIEW

CCT: Single (3000K-4000K-5000K) Applications: IP44 Efficacy: 70-75Im/W Dimming: TRIAC LED Type: SMD2835 Lens Type: Frosted Driver: Driver on board Operating Temp: -13° to 122° F Operating Humidity: 10% - 65% RH Lifespan: 50,000 Hours Warranty: 5 Years

FEATURES

- Flicker-Free
- CRI of 90 renders light temperatures consistently in various environments, giving colors true clarity
- Safe for damp locations such as bathrooms









Project:


Type:_

N a m e :____


Date:_

PHOTOMETRICS:

DL4



	Illuminance at a		
	Center Beam fc	Beam Wie	dth
1.7 R	74.7 fc	4.9 ft	4.8 ft
3.3ft	19.8 fc	9.4 ft	9.3 ft
5.0R	8.64 fc	14.3 ft	14.1 ft
6.7 R	4.81 fc	19.1 ft	18.9 ft
8.3R	3.13 fc	23.7 ft	23.5 ft
10.0 R	2.16 fc	28.6 ft	28.3 ft
	Vert. Spread: 110.0° Horiz. Spread: 109.5°		





	Illuminance at a Distance Center Beam fc Beam Width				
1.78	117 fc	5.9 ft	5.4 ft		
3.3R	31.2 fc	11.5 ft	10.4 ft		
5.0R	13.6 fc	17.4 ft	15.8 ft		
6.7ft	7.56 fc	23.3 ft	21.1 ft		
8.3ft	4.93 fc	28.9 ft	26.1 ft		
10.0 R	3.39 fc	34.8 ft	31.5 ft		
	Vert. Spread: 120.2° Horiz. Spread: 115.2°				


DL6















Project:	Туре:
N a m e :	Date:

ORDER FORM:

				(*) Specie	al Order/Not Com	monly Stocked
Custom Model Asser	mbly					
SES-DL4-3000-1 Example Model Numb		Fixture	CCT □ 3000K □ 4000K □ 5000K	Watts 10W 15W	Beam Angle 120°	Voltage 120V
Quantity	SES	Fixture		Watts	— 120° - Beam Angle	- 120V Voltage

Common Stock Models:

ltem #	Model #
11272	SES-DL4-3000-10
11273	SES-DL4-5000-10
11099	SES-DL6-3000-15-D
11100	SES-DL6-5000-15-D
30009	SES-DL6-4000-15-D

