

PANEL LIGHTS Name:_____

| F10ject | Project: | Туре: |
|---------|----------|-------|
|---------|----------|-------|

Date:_





| Size | 48" L x 24" W x 1.2" D |
|---------------|-------------------------|
| Watts | 72W |
| Voltage | 100-277V |
| Dimming | 3-in-1 (0-10V, PWM, Rx) |
| Beam Angle | 120° |
| CRI | >80 |
| PF | ≥ 0.95 |

| Lumens | 9000lm |
|-----------|--------------|
| ССТ | 6500K |
| IP Rating | IP40 |
| Materials | Aluminum, PS |
| Finish | White |
| Lens | Frosted |
| Lifespan | 50,000 Hours |

SARIN LED Backlit Panel Lights are a good solution to retrofit fluorescent tubes with advanced LED technology that includes dimming options. Designed to install quickly and easily in T-bar ceiling grids or pendants, these systems deliver all advantages of LED in a fixture accessible from below the ceiling plane. They are an excellent replacement for fluorescent lights and can provide an energy savings of up to 60%.

This Panel Light is intended only for indoor use. These lights are perfect for offices, schools, places of worship, and hospitals.

OVERVIEW

CCT: 6500K

Applications: IP40 Efficacy: 125lm/W

Dimming: 0-10V, PWM, Rx

LED Type: SMD2835

Lens Type: Frosted

Operating Temp: -68° to 104° F

Operating Humidity: <20%

Lifespan: 50,000 Hours

Warranty: 5 Years


FEATURES

- 3 in 1 dimming options allow for full control
- Easily installed in T-bar ceiling grids or pendant















BACKLIT PANEL LIGHTS

| Project: | Туре: |
|----------|-------------|
| , | ,, <u> </u> |

N a m e :__ Date:_

PHOTOMETRICS:






DIMENSIONS:









| Project: | Type: |
|----------|-------------|
| • | |
| Nama | Data. |

ORDER FORM:

(*) Special Order/Not Commonly Stocked

Custom Model Assembly

Voltage **Fixture** CCT Watts Beam Angle **▼** BL24 **₫** 6500K **7**2W 120° **✓** 100-277∨

SES-BL24-F72-50 Example Model Number

SES 120° **BL24** — 6500K — **72W** -100-277V Quantity Fixture CCT Watts Beam Angle Voltage

Common Stock Models:

| Item # | Model # |
|--------|-----------------|
| 10980 | SES-BL24-F72-50 |

