

### CCT Tunable Full Cut-Off Wall Pack

Project: \_\_\_\_





Size	15.4" x 14.1" x 9.4"	Lumens	13,350-13,544lm	
Watts	100W/80W/60W	сст	Tunable: 3000K+4000K+5000K	
Voltage	120-277V	IP Rating	IP65	
Dimming	0-10V	Materials	Die-cast aluminum	
Beam Angle	H120°/V82°	Finish	Bronze	
CRI	>80	Lens	Clear	
PF	≥0.9	Lifespan	50,000 hours	

SARIN LED FULL CUT-OFF WALL PACKS are commonly used to replace high-pressure sodium and metal halide lights to provide energy savings of up to 70%. These Wall Pack lights are safe for outdoor use and are protected from rain, snow, and weak jets of water, such as sprinklers. This light is both CCT Tunable and Wattage Selectable, featuring 3 different color temperatures and three different wattages to choose from.

This wall pack adopts the latest technology, replacing traditional bulbs with energy efficient LEDs. These are widely used in the lighting of homes, hotels, garages, streets, landscapes and other commercial spaces. These fixtures are suitable for a variety of applications and will provide significant energy savings. **OVERVIEW** 

Applications: In/Outdoor IP65 Efficacy: 130-150Im/w Dimming: 0-10V LED Type: SMD 2835 Lens Type: Clear Driver: BQE55-0510-118-PVF-PS Operating Temp: -40° to 122° F Operating Humidity: 20-95%RH Lifespan: 50,000 hours Warranty: 5 years

## **FEATURES**

- Photocell Light Sensor automatically activates the lights when dark
- CCT Tunable and Wattage
  Selectable
- Die-Cast Aluminum Casing for thermal management and durability
- Beautiful Powder Coated Bronze finish looks great in any location
- Corrosion-resistant design ideal for any extreme outdoor condition
- LEDs last for 50,000 hours.
- Bright and uniform, instant start, non-flickering, non-humming LEDs





Type: \_



CCT Tunable Full Cut-Off Wall Pack

Project:	
Name:	

Type: \_


Date:


#### Polar Candela Distribution 180° 170° 160° 150° 140° 5,600 4,667 130° 3,733 120° 2,800 110° 1,867 100° 933 CD: 0 90° 933 80° 1,867 70° 2,800 60° 3,733 50° 4,667 5,600 10° 20° 30° ■ - 22.5° H VA: 0° 40° – 0° H 📕 - 90° H - 45° H 🔳 - 67.5° H


**PHOTOMETRICS:** 


	Illuminance at a Center Beam fc	Distance Beam Wid	lth			
3.3R	396 fc	5.8 ft	12.3 ft			
6.7ft	96.2 fc	11.7 ft	25.0 ft			
10.0R	43.2 fc	17.5 ft	37.3 ft			
13.3R	24.4 fc 15.5 fc	23.3 ft 29.2 ft	49.6 ft 62.3 ft			
16.7R	10.8 fc	35.0 ft	74.6 ft			
	Vert. Spread: 82.4°					

# **DIMENSIONS**















Project:	Туре:		
-			
Name:	Date:		

## **ORDER FORM:**

				(*) Specio	al Order/Not Com	monly Stocked
Custom Model Asse	mbly					
<u>SES-FWP06-CCT-100/</u> Example Model Numb		Fixture ☑ FWP06	сст и зооок и 4000к и 5000к	Watts      ✓    60W      ✓    80W      ✓    100W	Beam Angle ☑ 110°	<b>Voltage</b> ☑ 120-277V
	SES	- FWP06 -	- ССТ	- ADJ	– <b>110°</b> -	- 120-277V
Quantity		Fixture	ССТ	Watts	Beam Angle	Voltage

## **Common Stock Models:**

Item #	Model #	Туре
11456	SES-FWP06-CCT-100/80/60	CCT Tunable/Wattage Adjustable Full Cut-Off Wall Pack

