



SSL

# LED ADJUSTABLE SOLAR AREA LIGHT

Project: \_\_\_\_\_ Type: \_\_\_\_\_

Name: \_\_\_\_\_ Date: \_\_\_\_\_



<b>Size</b>	See Dimensions	<b>Lumens</b>	10,200lm, 13,800lm
<b>Watts</b>	60W, 80W	<b>CCT</b>	6000K
<b>Voltage</b>	DC17.5V	<b>IP Rating</b>	IP65
<b>Dimming</b>	PIR Motion Sensor	<b>Materials</b>	Aluminum, ABS, PC
<b>Beam Angle</b>	140°xw70°	<b>Finish</b>	Black
<b>LiFeP04 Battery</b>	32700, 115.2Wh 32700, 153.6Wh	<b>Lens</b>	Clear
<b>Charge Time</b>	7 Hours	<b>PIR Sensor</b>	120° / 26' Detection
<b>Working Time</b>	3-4 nights depending on mode	<b>Lifespan</b>	35,000 Hours

## OVERVIEW

- Tunable:** 6000K
- Applications:** IP65
- Efficacy:** 170lm/W
- Dimming:** Motion Sensor
- Operating Temp:** -4° to 140°
- Lifespan:** 35,000 Hours
- Warranty:** 3-Year Product and Battery Warranty

## FEATURES

- Remote control
- Protected from the elements with an IP65 rating, making it suitable for rainy environments

SARIN Solar Area Lights are designed with adjustable light modules to allow the optimal angle for sunlight absorption and light spread. The premium quality mono-crystalline silicon solar panel has high efficiency solar power conversion. The remote is used to switch between a variety of working modes. There are two PIR motion sensors for use with the motion detection setting with increased range.

This decorative solar area light is ideal for parking lots, street lighting, sidewalks and parks. With an IP65 rating, they are safe to use in wet locations that come in direct contact with rain and water.





SSL

# LED ADJUSTABLE SOLAR AREA LIGHT


Project: \_\_\_\_\_ Type: \_\_\_\_\_

Name: \_\_\_\_\_ Date: \_\_\_\_\_

## PHOTOMETRICS:

X° Beam Angle: (Polar Candela Dist. )

Light Distance: (Illuminance at a Distance)




**Illuminance at a Distance**

	Center Beam fc	Beam Width	
4.3ft	146 fc	25.7 ft	4.1 ft
8.7ft	35.6 fc	52.0 ft	8.2 ft
13.0ft	16.0 fc	77.6 ft	12.3 ft
17.3ft	9.01 fc	103.3 ft	16.4 ft
21.7ft	5.73 fc	129.6 ft	20.6 ft
26.0ft	3.99 fc	155.3 ft	24.7 ft


Vert. Spread: 143.0°  
Horiz. Spread: 50.7°

## DIMENSIONS:

60W



80W





SSL

# LED ADJUSTABLE SOLAR AREA LIGHT

Project: \_\_\_\_\_ Type: \_\_\_\_\_

Name: \_\_\_\_\_ Date: \_\_\_\_\_

## ORDER FORM:

(\* Special Order/Not Commonly Stocked)

Custom Model Assembly

	Fixture	CCT	Watts	Beam Angle	Voltage
<input checked="" type="checkbox"/> SSL	<input checked="" type="checkbox"/> 6000K	<input type="checkbox"/> 60W	<input checked="" type="checkbox"/> 140°	<input checked="" type="checkbox"/> DC17.5V	
		<input type="checkbox"/> 80W			

SES-SSL-60  
Example Model Number

	<b>SES</b>	-	<b>SSL</b>	-	<b>6000K</b>	-	<b>140°</b>	-	<b>17.5V</b>
Quantity	Fixture		CCT		Watts		Beam Angle		Voltage

### Common Stock Models:

Item #	Model #
11473	SES-SSL-60-WING
11474	SES-SSL-80-WING