

Ρ	ro	ie	С	t	
•		10	~	۰.	•

Name:

Date:

2719

OVERVIEW

CCT: 3000K+4000K+5000K Applications: IP65 Efficacy: 110lm/W Dimming: 0-10V LED Type: COB Lens Type: Clear Driver: HB-FL19F080B Operating Temp: -31F° to 122F° Operating Humidity: 10%-65% RH Lifespan: 50,000 Hours Warranty: 5 Years

FEATURES

- Protected from the elements with an IP65 rating, making it suitable for rainy environments
- 5-Year Warranty, rated to last up to 50,000 hours





Size	14.17" x 4.72" x 5.83"	Lumens	7,920lm @4000K	
Watts	72W	сст	3000K+4000K+5000K	
Voltage	120-277V	IP Rating	IP65	
Dimming	0-10V	Materials	Aluminum, Glass, PC lens	
Beam Angle	25°	Finish	Bronze	
CRI	>80	Lens	Clear	
PF	0.9	Lifespan	50,000 Hours	

SARIN LED Up-Down Wall Lights are excellent for adding lighting to any wall. Modernize the exterior lighting of your residential or commercial space with this sleek looking LED wall sconce. Constructed of rugged, aluminum, this outdoor wall wash light is durable and suitable for wet locations to withstand the elements.

LED Up-Down Wall Lights are perfect for hotels, shopping centers, and hospitals.





Project:	Type:

ORDER FORM:

Custom Model Assembly			(*) Specio	al Order/Not Com	nmonly Stocked
SES-UDWP01C-CCT-72-25 Example Model Number	Fixture ☑ UDWP	ССТ	Watts ₽ 72W	Beam Angle ☑ 25°	Voltage ☑ 120-277V
SES		- CCT	- 72W		- 120-277V
Quantity	Fixture	ССТ	Watts	Beam Angle	Voltage

Common Stock Models:

ltem #	Model #
11481	SES-UDWP01C-CCT-72-25

