



Project:

Type:_

N a m e :_____

Date:____



Size	14.17" x 4.72" x 5.83"	Lumens	3600-4140lm	
Watts	36W	сст	RGB	CCT: RC
Voltage	100-277V	IP Rating	IP65	Efficacy
Dimming	0-10V	Materials	Aluminum, Glass, PC lens	Dimmin LED Typ
Beam Angle	45°	Finish	Bronze	Lens Ty
CRI	>80	Lens	Clear	Driver: Operat
PF	0.9	Lifespan	35,000 Hours	Operat

SARIN LED Up-Down Wall Lights are excellent for adding lighting to any wall. Modernize the exterior lighting of your residential or commercial space with this sleek looking LED wall sconce. Constructed of rugged, aluminum, this outdoor wall wash light is durable and suitable for wet locations to withstand the elements.

LED Up-Down Wall Lights are perfect for hotels, shopping centers, and hospitals.

OVERVIEW

CCT: RGB Applications: IP65 Efficacy: RGB Dimming: Non-Dimming LED Type: 3-in-1 chip Lens Type: Clear Driver: UL Driver Operating Temp: -40F° to 113F° Operating Humidity: 10%-65% RH Lifespan: 35,000 Hours Warranty: 3 Years

FEATURES

- Protected from the elements with an IP65 rating, making it suitable for rainy environments
- 3-Year Warranty, rated to last up to 35,000 hours





		GB WALL CONCE		t:		
ORDER FORM:				(*) Specie	al Order/Not Com	monly Stocked
Custom Model Asse	embly					
SES-UDWP01B-RGB-36 Example Model Num		Fixture	ССТ ✔ RGB	Watts ∎ 36W	Beam Angle ☑ 45°	Voltage 120-277V
	SES	- UDWP	– сст	– 36W	– 45 ° -	– 120-277V
Quantity		Fixture	CCT	Watts	Beam Angle	Voltage

Common Stock Models:

ltem #	Model #
11444	SES-UDWP01B-RGB-36W-15-BZ

