Report No.: Test Time: 2024/3/22 星期五 00:38

Luminaire Property


Luminaire Manufacturer:
Number of Lamps: 1
Lumens per Lamp: 8041.6 lm
Luminous Length (mm): 0 mm
Luminous Width (mm): 0 mm
Luminous Height (mm): 0 mm
Voltage: 120.0 V
Current: 0.498 A
Power: 59.80 W
Power Factor: 0.991

Photometric Results

CIE Class: Direct
Total Rated Lamp Lumens: 8041.6 lm
Measurement Flux: 8041.7 lm
Efficiency: 100.00%
Downward Ratio: 99.16%
Upward Ratio: 0.84%
Horizontal Diffuse Angle(10%,50%): H154.1,H93.1
Vertical Diffuse Angle(10%,50%): V158.5,V101
Luminaire Efficacy Rating (LER): 134.53
Central Intensity: 3301.48 cd
Max. Intensity: 3309.22 cd
Pos of Max. Intensity: H22.5 V1
S/MH(C0/C180): 1.13
S/MH(C90/C270): 1.19

Picture Of Luminaire


Luminous Intensity Distribution Curve




Unit: cd
Average Diffuse Angle(50%): 97.0°
C0-C180 C90-C270 G1

C Plane (°):0.0-360.0: 22.5
Gamma Plane (°):0.0-180.0:1.0
Test Lab:
Test Device: GPM-1800B
Test Type: TYPE C
Distance: 8.190 m
Temperature:
Humidity:
Operator:
Inspector:

Luminous Intensity Distribution Curve






C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:


Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	109	105	100	97	106	102	98	95	98	95	92	94	91	89	90	88	86	84
2	100	92	85	80	97	90	84	79	86	81	77	83	79	75	80	76	73	71
3	91	81	73	67	89	79	72	66	76	70	65	73	68	64	71	66	63	60
4	84	72	64	57	81	71	63	57	68	61	56	66	60	55	64	58	54	52
5	77	65	56	50	75	64	55	49	61	54	49	59	53	48	57	52	48	45
6	72	59	50	44	70	58	49	43	56	48	43	54	47	43	52	47	42	40
7	66	53	45	39	65	52	44	39	51	44	38	49	43	38	48	42	38	36
8	62	49	40	35	60	48	40	35	47	39	34	45	39	34	44	38	34	32
9	58	45	37	31	57	44	37	31	43	36	31	42	36	31	41	35	31	29
10	54	41	34	29	53	41	34	29	40	33	28	39	33	28	38	32	28	26

Spacing Criteria (0-180): 1.13
Spacing Criteria (90-270): 1.19
Spacing Criteria (Diagonal): 1.26


Curves of Luminaires vs Lighting Area



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Isocandela (rectangle)




Imax (100%): 3309 cd

(10%): 331 cd
(16%): 529 cd
(25%): 827 cd
(40%): 1324 cd
(63%): 2085 cd
(100%): 3309 cd

C Plane (°):0.0-360.0: 22.5
Gamma Plane (°):0.0-180.0:1.0
Test Lab:
Test Device: GPM-1800B
Test Type: TYPE C
Distance: 8.190 m
Temperature:
Humidity:
Operator:
Inspector:

Isocandela (sphere)




Imax (100%): 3309 cd

(10%): 331 cd	(16%): 529 cd
(25%): 827 cd	(40%): 1324 cd
(63%): 2085 cd	(100%): 3309 cd

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 33.1 lx

(1%): 0.3 lx	(2%): 0.7 lx
(5%): 1.7 lx	(10%): 3.3 lx
(20%): 6.6 lx	(50%): 16.5 lx
(90%): 29.8 lx	(100%): 33.1 lx

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Roadway CU Curve





C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h






L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	1811	1556	1311	1078	853	646	454	284	136
C90	1948	1697	1443	1194	954	728	514	324	154
C180	1654	1405	1167	938	725	527	345	190	61
C270	1906	1655	1397	1149	907	685	472	284	119

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Illuminance at a Distance(Beam Angle)




Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
1.0	3301.48	2.11/2.43	4.0	742.32
2.0	825.37	4.22/4.85	16.2	185.58
3.0	366.83	6.33/7.28	36.4	82.48
4.0	206.34	8.45/9.70	64.7	46.40
5.0	132.06	10.56/12.13	101.0	29.69
6.0	91.71	12.67/14.55	145.5	20.62
7.0	67.38	14.78/16.98	198.0	15.15
8.0	51.59	16.89/19.40	258.6	11.60
9.0	40.76	19.00/21.83	327.3	9.16
10.0	33.01	21.11/24.25	404.1	7.42

Beam Angle(B): H93.1 V101.0 Field Angle(F): H154.1 V158.5

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Illuminance at a Distance(Field Angle)




Dist(m)	Enadir(lx)	Dh/Dv_F(m)	S_F(sq.m)	Eav_F(lx)
1.0	3301.48	8.69/10.54	73.2	25.20
2.0	825.37	17.39/21.08	292.6	6.30
3.0	366.83	26.08/31.63	658.5	2.80
4.0	206.34	34.77/42.17	1170.6	1.58
5.0	132.06	43.47/52.71	1829.1	1.01
6.0	91.71	52.16/63.25	2633.8	0.70
7.0	67.38	60.85/73.79	3584.9	0.51
8.0	51.59	69.55/84.34	4682.4	0.39
9.0	40.76	78.24/94.88	5926.1	0.31
10.0	33.01	86.93/105.42	7316.2	0.25

Beam Angle(B): H93.1 V101.0 Field Angle(F): H154.1 V158.5

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 3301.5 lx

(1%): 33.0 lx	(2%): 66.0 lx
(5%): 165.1 lx	(10%): 330.1 lx
(20%): 660.3 lx	(50%):1650.7 lx
(90%):2971.3 lx	(100%):3301.5 lx

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Area Flux Table

Unit: lm

Vertical plane	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
-90	0.0	0.1	0.2	0.6	1.1	1.8	2.5	3.2	3.6	3.8	3.5	3.0	2.3	1.6	1.0	0.5	0.2	0.1	29.1	0.0	
-80	0.0	0.3	1.3	3.0	5.3	8.0	10.6	12.8	14.1	14.3	13.3	11.4	8.8	6.1	3.7	1.8	0.7	0.1	115.6	79.7	
-70	0.1	0.8	2.8	6.1	10.5	15.5	20.6	24.7	27.1	27.4	25.4	21.5	16.6	11.5	6.9	3.4	1.2	0.2	222.1	211.1	
-60	0.1	1.3	4.3	9.4	16.1	23.8	31.5	37.9	41.7	42.0	38.8	32.8	25.1	17.2	10.3	5.0	1.8	0.3	339.3	333.4	
-50	0.2	1.8	5.8	12.6	21.7	32.2	42.8	51.6	56.9	57.2	52.7	44.2	33.7	23.0	13.6	6.7	2.3	0.3	459.3	455.5	
-40	0.2	2.2	7.2	15.5	26.8	40.0	53.5	64.8	71.4	71.9	66.1	55.1	41.7	28.2	16.7	8.2	2.8	0.4	572.7	570.0	
-30	0.2	2.5	8.3	17.9	31.0	46.6	62.6	76.1	84.0	84.4	77.4	64.5	48.5	32.7	19.4	9.5	3.2	0.4	669.5	667.2	
-20	0.3	2.8	9.1	19.7	34.1	51.4	69.3	84.3	93.0	93.5	85.6	71.2	53.6	36.3	21.6	10.5	3.5	0.5	740.3	738.4	
-10	0.3	2.9	9.5	20.5	35.6	53.8	72.7	88.6	97.9	98.3	90.2	75.4	57.1	38.6	22.8	11.0	3.7	0.5	779.4	777.5	
0	0.3	2.9	9.6	20.6	35.9	54.3	73.3	89.2	98.1	98.7	90.9	76.1	57.6	38.9	23.0	11.1	3.7	0.5	784.7	783.1	
10	0.3	2.9	9.4	20.2	35.0	52.8	70.7	85.4	93.6	94.0	86.5	72.5	54.9	37.2	22.0	10.7	3.6	0.5	752.0	750.1	
20	0.2	2.7	8.7	18.7	32.3	48.2	64.1	77.3	84.9	85.2	78.3	65.7	49.9	33.9	20.2	9.8	3.3	0.4	683.9	681.8	
30	0.2	2.3	7.7	16.5	28.1	41.5	55.0	66.3	72.6	72.9	67.1	56.3	42.9	29.4	17.6	8.6	3.0	0.4	588.5	586.0	
40	0.2	1.9	6.4	13.6	22.9	33.6	44.3	53.2	58.2	58.5	53.9	45.4	34.8	24.0	14.5	7.2	2.5	0.3	475.5	472.1	
50	0.1	1.5	4.9	10.3	17.3	25.2	33.1	39.5	43.1	43.3	40.0	33.9	26.2	18.2	11.1	5.5	2.0	0.3	355.5	350.5	
60	0.1	1.0	3.3	6.9	11.6	16.8	22.0	26.1	28.6	28.7	26.6	22.7	17.6	12.4	7.6	3.9	1.4	0.2	237.5	228.3	
70	0.0	0.5	1.8	3.7	6.2	9.1	11.9	14.1	15.5	15.6	14.4	12.4	9.7	6.9	4.3	2.2	0.9	0.1	129.4	99.7	
80	0.0	0.1	0.5	1.0	1.7	2.6	3.4	4.2	4.7	4.7	4.4	3.8	3.0	2.2	1.4	0.8	0.4	0.1	39.1	0.0	
90	2.8	30.5	100.8	216.7	373.2	557.3	744.2	899.2	989.0	994.5	915.0	767.8	584.0	398.3	237.5	116.6	40.3	5.6	7973		
Flux(T)	0.0	13.9	88.5	205.3	362.4	546.8	733.9	889.0	979.1	985.1	904.5	757.8	573.6	387.5	226.4	104.8	25.7	0.0		7785	
Flux(E)																					


Horizontal plane

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

The Average Illuminance Effective Figure

Flux Out: 4860.46lm



Height	Avg./Nadir. E	Beam Angle:93.1°	Diameter / Area
2.0m	347.05/ 825.37lx		4.22m / 14.00sq.m
3.0m	154.25/ 366.83lx		6.33m / 31.51sq.m
4.0m	86.76/ 206.34lx		8.45m / 56.02sq.m
5.0m	55.53/ 132.06lx		10.56m / 87.53sq.m
6.0m	38.56/ 91.71lx		12.67m / 126.04sq.m
7.0m	28.33/ 67.38lx		14.78m / 171.56sq.m
8.0m	21.69/ 51.59lx		16.89m / 224.08sq.m
9.0m	17.14/ 40.76lx		19.00m / 283.60sq.m
10.0m	13.88/ 33.01lx		21.11m / 350.12sq.m
22.0m	2.87/ 6.82lx		46.45m / 1694.60sq.m

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
3H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
4H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
6H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
8H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
12H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
X=4H Y=2H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
3H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
4H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
6H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
8H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
12H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
X=8H Y=4H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
6H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
8H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
12H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
X=12H Y=4H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
6H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
8H	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$	-1.$
Variations with the observer position at spacings:										
S=1.0H	-1.$/-1.$					-1.$/-1.$				
S=1.5H	-1.$/-1.$					-1.$/-1.$				
S=2.0H	-1.$/-1.$					-1.$/-1.$				

Calculate in accordance with CIE Pub.117. The table is revised with 8042lm (8log(F/F0) = 7.2).

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM




ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	4046	50.3
FL (0°-30°)	1236	15.4
FM (30°-60°)	2054	25.5
FH (60°-80°)	683	8.5
FVH (80°-90°)	73	0.9
BACK LIGHT	3928	48.8
BL (0°-30°)	1225	15.2
BM (30°-60°)	2003	24.9
BH (60°-80°)	642	8.0
BVH (80°-90°)	58	0.7
UP LIGHT	68	0.8
UL (90°-100°)	4	0.1
UH (100°-180°)	63	0.8
TRAPPED LIGHT	NA	NA

BUG(**B**acklight,**U**plight,**G**lare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B3 U2 G2
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B3 U2 G1

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

LCS Graph



Scale= MAX LCS%

Trapped Light:NA,NA

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.60	0.70	0.77	0.82	0.89	0.94	0.97	1.01	1.04
	0.30		0.52	0.62	0.70	0.75	0.83	0.88	0.92	0.97	1.01
	0.20		0.47	0.57	0.64	0.70	0.78	0.84	0.88	0.94	0.98
0.50	0.50	0.20	0.58	0.68	0.74	0.79	0.86	0.90	0.93	0.97	1.00
	0.30		0.51	0.61	0.68	0.73	0.81	0.86	0.89	0.94	0.97
	0.20		0.46	0.56	0.63	0.69	0.76	0.82	0.86	0.91	0.94
0.30	0.50	0.20	0.56	0.66	0.72	0.76	0.83	0.87	0.90	0.93	0.96
	0.30		0.50	0.60	0.67	0.72	0.78	0.83	0.86	0.91	0.93
	0.20		0.46	0.56	0.62	0.68	0.75	0.80	0.83	0.88	0.91
0.00	0.00	0.00	0.44	0.53	0.60	0.64	0.71	0.76	0.79	0.84	0.86

Rating:60W Photometrically tested without ceiling board.

Multiply UF values by service correction factors

Calculate in accordance with CIBSE Technical Memorandum NO.5 1980

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.95	0.78	0.66	0.58	0.46	0.38	0.33	0.25	0.21
	0.30		0.79	0.67	0.58	0.51	0.42	0.35	0.30	0.24	0.20
	0.20		0.68	0.58	0.51	0.46	0.38	0.32	0.28	0.22	0.19
0.50	0.50	0.20	0.92	0.75	0.64	0.55	0.44	0.40	0.31	0.24	0.20
	0.30		0.77	0.65	0.56	0.49	0.40	0.34	0.29	0.23	0.19
	0.20		0.67	0.57	0.50	0.45	0.37	0.31	0.27	0.22	0.18
0.30	0.50	0.20	0.89	0.72	0.61	0.53	0.42	0.35	0.29	0.23	0.19
	0.30		0.76	0.63	0.54	0.48	0.39	0.32	0.28	0.22	0.18
	0.20		0.66	0.57	0.49	0.44	0.36	0.30	0.26	0.21	0.17
0.00	0.00	0.00	0.56	0.46	0.40	0.35	0.28	0.23	0.20	0.16	0.13

Rating:60W Photometrically tested without ceiling board.

Multiply UF values by service correction factors

Calculate in accordance with CIBSE Technical Memorandum NO.5 1980

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.17	0.18	0.19	0.20	0.21	0.21	0.22	0.22	0.23
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20
	0.20		0.06	0.07	0.09	0.10	0.12	0.14	0.15	0.17	0.18
0.50	0.50	0.20	0.16	0.17	0.18	0.19	0.20	0.20	0.21	0.21	0.22
	0.30		0.10	0.12	0.13	0.14	0.15	0.17	0.17	0.19	0.19
	0.20		0.05	0.07	0.09	0.10	0.12	0.13	0.14	0.16	0.17
0.30	0.50	0.20	0.16	0.17	0.18	0.18	0.19	0.20	0.20	0.20	0.21
	0.30		0.10	0.11	0.13	0.14	0.15	0.16	0.17	0.18	0.19
	0.20		0.05	0.07	0.09	0.10	0.12	0.13	0.14	0.16	0.17
0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01

Rating:60W Photometrically tested without ceiling board.

Multiply UF values by service correction factors

Calculate in accordance with CIBSE Technical Memorandum NO.5 1980

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	3301.3	3.2	3.2	0.04	0.04
1.0-2.0	3299.7	9.5	12.6	0.12	0.16
2.0-3.0	3295.6	15.8	28.4	0.20	0.35
3.0-4.0	3290.2	22.0	50.4	0.27	0.63
4.0-5.0	3283.5	28.3	78.7	0.35	0.98
5.0-6.0	3274.2	34.4	113.1	0.43	1.41
6.0-7.0	3262.6	40.5	153.6	0.50	1.91
7.0-8.0	3250.5	46.5	200.1	0.58	2.49
8.0-9.0	3237.0	52.5	252.6	0.65	3.14
9.0-10.0	3221.1	58.3	310.9	0.72	3.87
10.0-11.0	3203.5	64.0	374.9	0.80	4.66
11.0-12.0	3184.4	69.6	444.5	0.87	5.53
12.0-13.0	3163.5	75.1	519.6	0.93	6.46
13.0-14.0	3140.5	80.4	600.0	1.00	7.46
14.0-15.0	3116.1	85.6	685.6	1.06	8.53
15.0-16.0	3090.9	90.6	776.1	1.13	9.65
16.0-17.0	3063.6	95.4	871.6	1.19	10.84
17.0-18.0	3034.5	100.1	971.6	1.24	12.08
18.0-19.0	3004.3	104.5	1076.2	1.30	13.38
19.0-20.0	2972.6	108.8	1185.0	1.35	14.74
20.0-21.0	2939.4	112.9	1297.9	1.40	16.14
21.0-22.0	2905.2	116.8	1414.6	1.45	17.59
22.0-23.0	2869.3	120.4	1535.0	1.50	19.09
23.0-24.0	2831.7	123.8	1658.9	1.54	20.63
24.0-25.0	2793.4	127.0	1785.9	1.58	22.21
25.0-26.0	2754.2	130.0	1915.9	1.62	23.83
26.0-27.0	2713.8	132.8	2048.7	1.65	25.48
27.0-28.0	2672.5	135.3	2184.0	1.68	27.16
28.0-29.0	2629.5	137.6	2321.6	1.71	28.87
29.0-30.0	2585.2	139.6	2461.2	1.74	30.61
30.0-31.0	2540.9	141.4	2602.6	1.76	32.36
31.0-32.0	2495.8	143.0	2745.6	1.78	34.14
32.0-33.0	2449.6	144.3	2890.0	1.79	35.94
33.0-34.0	2402.5	145.4	3035.4	1.81	37.75
34.0-35.0	2354.9	146.3	3181.7	1.82	39.56
35.0-36.0	2306.8	146.9	3328.5	1.83	41.39

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	2257.9	147.3	3475.8	1.83	43.22
37.0-38.0	2209.3	147.5	3623.3	1.83	45.06
38.0-39.0	2159.8	147.4	3770.8	1.83	46.89
39.0-40.0	2109.6	147.2	3917.9	1.83	48.72
40.0-41.0	2059.0	146.6	4064.6	1.82	50.54
41.0-42.0	2008.3	145.9	4210.5	1.81	52.36
42.0-43.0	1957.9	145.1	4355.5	1.80	54.16
43.0-44.0	1907.2	144.0	4499.5	1.79	55.95
44.0-45.0	1856.1	142.7	4642.2	1.77	57.73
45.0-46.0	1804.6	141.1	4783.3	1.76	59.48
46.0-47.0	1753.7	139.5	4922.8	1.73	61.22
47.0-48.0	1703.4	137.7	5060.5	1.71	62.93
48.0-49.0	1652.3	135.7	5196.2	1.69	64.62
49.0-50.0	1601.6	133.6	5329.8	1.66	66.28
50.0-51.0	1551.6	131.3	5461.1	1.63	67.91
51.0-52.0	1501.3	128.8	5589.9	1.60	69.51
52.0-53.0	1451.3	126.3	5716.2	1.57	71.08
53.0-54.0	1402.1	123.6	5839.8	1.54	72.62
54.0-55.0	1353.1	120.8	5960.6	1.50	74.12
55.0-56.0	1303.7	117.8	6078.4	1.47	75.59
56.0-57.0	1254.9	114.8	6193.1	1.43	77.01
57.0-58.0	1206.8	111.6	6304.8	1.39	78.40
58.0-59.0	1158.7	108.3	6413.1	1.35	79.75
59.0-60.0	1111.2	105.0	6518.1	1.31	81.05
60.0-61.0	1064.5	101.6	6619.7	1.26	82.32
61.0-62.0	1017.9	98.1	6717.8	1.22	83.54
62.0-63.0	971.9	94.5	6812.3	1.18	84.71
63.0-64.0	926.4	90.9	6903.2	1.13	85.84
64.0-65.0	881.0	87.2	6990.4	1.08	86.93
65.0-66.0	836.5	83.5	7073.9	1.04	87.97
66.0-67.0	792.7	79.7	7153.6	0.99	88.96
67.0-68.0	749.3	75.9	7229.5	0.94	89.90
68.0-69.0	706.4	72.1	7301.6	0.90	90.80
69.0-70.0	664.7	68.3	7369.9	0.85	91.65
70.0-71.0	623.5	64.4	7434.3	0.80	92.45
71.0-72.0	582.1	60.5	7494.9	0.75	93.20

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	542.1	56.7	7551.6	0.71	93.91
73.0-74.0	503.0	52.9	7604.4	0.66	94.56
74.0-75.0	464.1	49.0	7653.5	0.61	95.17
75.0-76.0	426.5	45.3	7698.8	0.56	95.74
76.0-77.0	389.9	41.6	7740.4	0.52	96.25
77.0-78.0	353.9	37.9	7778.2	0.47	96.73
78.0-79.0	318.8	34.3	7812.5	0.43	97.15
79.0-80.0	284.4	30.7	7843.2	0.38	97.53
80.0-81.0	250.7	27.1	7870.3	0.34	97.87
81.0-82.0	218.1	23.7	7893.9	0.29	98.16
82.0-83.0	186.8	20.3	7914.2	0.25	98.42
83.0-84.0	156.4	17.0	7931.3	0.21	98.63
84.0-85.0	127.1	13.9	7945.2	0.17	98.80
85.0-86.0	99.4	10.9	7956.0	0.14	98.94
86.0-87.0	73.3	8.0	7964.1	0.10	99.04
87.0-88.0	49.3	5.4	7969.5	0.07	99.10
88.0-89.0	29.0	3.2	7972.6	0.04	99.14
89.0-90.0	14.0	1.5	7974.2	0.02	99.16
90.0-91.0	6.0	0.7	7974.8	0.01	99.17
91.0-92.0	3.6	0.4	7975.2	0.00	99.17
92.0-93.0	3.3	0.4	7975.6	0.00	99.18
93.0-94.0	3.3	0.4	7976.0	0.00	99.18
94.0-95.0	3.5	0.4	7976.3	0.00	99.19
95.0-96.0	3.7	0.4	7976.7	0.01	99.19
96.0-97.0	3.9	0.4	7977.2	0.01	99.20
97.0-98.0	4.1	0.4	7977.6	0.01	99.20
98.0-99.0	4.3	0.5	7978.1	0.01	99.21
99.0-100.0	4.5	0.5	7978.6	0.01	99.22
100.0-101.0	4.7	0.5	7979.1	0.01	99.22
101.0-102.0	5.0	0.5	7979.6	0.01	99.23
102.0-103.0	5.2	0.6	7980.2	0.01	99.24
103.0-104.0	5.3	0.6	7980.7	0.01	99.24
104.0-105.0	5.6	0.6	7981.3	0.01	99.25
105.0-106.0	5.9	0.6	7982.0	0.01	99.26
106.0-107.0	6.1	0.6	7982.6	0.01	99.27
107.0-108.0	6.4	0.7	7983.3	0.01	99.27

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	6.7	0.7	7984.0	0.01	99.28
109.0-110.0	6.9	0.7	7984.7	0.01	99.29
110.0-111.0	7.1	0.7	7985.4	0.01	99.30
111.0-112.0	7.4	0.8	7986.2	0.01	99.31
112.0-113.0	7.7	0.8	7986.9	0.01	99.32
113.0-114.0	8.0	0.8	7987.8	0.01	99.33
114.0-115.0	8.3	0.8	7988.6	0.01	99.34
115.0-116.0	8.5	0.8	7989.4	0.01	99.35
116.0-117.0	8.8	0.9	7990.3	0.01	99.36
117.0-118.0	9.0	0.9	7991.2	0.01	99.37
118.0-119.0	9.3	0.9	7992.0	0.01	99.38
119.0-120.0	9.6	0.9	7993.0	0.01	99.40
120.0-121.0	9.8	0.9	7993.9	0.01	99.41
121.0-122.0	10.1	0.9	7994.8	0.01	99.42
122.0-123.0	10.4	1.0	7995.8	0.01	99.43
123.0-124.0	10.8	1.0	7996.8	0.01	99.44
124.0-125.0	11.1	1.0	7997.8	0.01	99.46
125.0-126.0	11.3	1.0	7998.8	0.01	99.47
126.0-127.0	11.6	1.0	7999.8	0.01	99.48
127.0-128.0	11.9	1.0	8000.9	0.01	99.49
128.0-129.0	12.3	1.1	8001.9	0.01	99.51
129.0-130.0	12.5	1.1	8003.0	0.01	99.52
130.0-131.0	12.7	1.1	8004.0	0.01	99.53
131.0-132.0	13.1	1.1	8005.1	0.01	99.55
132.0-133.0	13.3	1.1	8006.2	0.01	99.56
133.0-134.0	13.7	1.1	8007.3	0.01	99.57
134.0-135.0	14.0	1.1	8008.4	0.01	99.59
135.0-136.0	14.2	1.1	8009.4	0.01	99.60
136.0-137.0	14.5	1.1	8010.5	0.01	99.61
137.0-138.0	14.8	1.1	8011.6	0.01	99.63
138.0-139.0	15.1	1.1	8012.7	0.01	99.64
139.0-140.0	15.4	1.1	8013.8	0.01	99.65
140.0-141.0	15.6	1.1	8014.9	0.01	99.67
141.0-142.0	15.9	1.1	8016.0	0.01	99.68
142.0-143.0	16.2	1.1	8017.1	0.01	99.70
143.0-144.0	16.5	1.1	8018.2	0.01	99.71

Zonal Lumen (Continue 4)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	16.8	1.1	8019.2	0.01	99.72
145.0-146.0	17.1	1.1	8020.3	0.01	99.73
146.0-147.0	17.3	1.0	8021.3	0.01	99.75
147.0-148.0	17.5	1.0	8022.4	0.01	99.76
148.0-149.0	17.8	1.0	8023.4	0.01	99.77
149.0-150.0	18.1	1.0	8024.4	0.01	99.79
150.0-151.0	18.4	1.0	8025.4	0.01	99.80
151.0-152.0	18.6	1.0	8026.4	0.01	99.81
152.0-153.0	18.9	1.0	8027.3	0.01	99.82
153.0-154.0	19.1	0.9	8028.2	0.01	99.83
154.0-155.0	19.4	0.9	8029.2	0.01	99.85
155.0-156.0	19.7	0.9	8030.1	0.01	99.86
156.0-157.0	19.9	0.9	8030.9	0.01	99.87
157.0-158.0	20.1	0.8	8031.8	0.01	99.88
158.0-159.0	20.3	0.8	8032.6	0.01	99.89
159.0-160.0	20.5	0.8	8033.4	0.01	99.90
160.0-161.0	20.7	0.8	8034.1	0.01	99.91
161.0-162.0	21.0	0.7	8034.9	0.01	99.92
162.0-163.0	21.1	0.7	8035.6	0.01	99.92
163.0-164.0	21.4	0.7	8036.2	0.01	99.93
164.0-165.0	21.6	0.6	8036.9	0.01	99.94
165.0-166.0	21.8	0.6	8037.5	0.01	99.95
166.0-167.0	22.0	0.6	8038.0	0.01	99.96
167.0-168.0	22.2	0.5	8038.6	0.01	99.96
168.0-169.0	22.4	0.5	8039.0	0.01	99.97
169.0-170.0	22.6	0.5	8039.5	0.01	99.97
170.0-171.0	22.7	0.4	8039.9	0.01	99.98
171.0-172.0	22.8	0.4	8040.3	0.00	99.98
172.0-173.0	22.9	0.3	8040.6	0.00	99.99
173.0-174.0	23.0	0.3	8040.9	0.00	99.99
174.0-175.0	23.2	0.2	8041.1	0.00	99.99
175.0-176.0	23.4	0.2	8041.3	0.00	100.00
176.0-177.0	23.5	0.2	8041.5	0.00	100.00
177.0-178.0	23.5	0.1	8041.6	0.00	100.00
178.0-179.0	23.6	0.1	8041.7	0.00	100.00
179.0-180.0	23.7	0.0	8041.7	0.00	100.00

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G0.0	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5
G1.0	3304.6	3309.2	3306.4	3300.3	3300.6	3300.4	3298.3	3301.1	3299.0	3302.9
G2.0	3306.0	3304.9	3301.1	3303.3	3295.1	3298.7	3298.3	3298.7	3291.4	3298.6
G3.0	3302.9	3305.7	3300.9	3294.0	3289.8	3293.8	3292.0	3291.1	3286.4	3288.0
G4.0	3297.3	3299.0	3297.8	3292.8	3283.4	3290.2	3284.1	3284.0	3274.5	3282.9
G5.0	3296.1	3293.5	3286.1	3288.9	3279.7	3284.1	3275.5	3276.1	3262.3	3273.4
G6.0	3284.7	3280.9	3280.9	3277.6	3265.7	3270.0	3266.7	3265.6	3246.0	3259.6
G7.0	3274.1	3270.3	3272.0	3268.6	3260.1	3261.0	3255.1	3251.7	3230.4	3243.1
G8.0	3260.2	3261.3	3264.1	3259.1	3248.8	3248.1	3242.2	3237.2	3211.8	3225.1
G9.0	3247.9	3246.7	3243.7	3246.6	3241.7	3236.7	3225.5	3221.3	3194.8	3203.4
G10.0	3229.5	3231.3	3230.2	3228.1	3225.2	3223.1	3207.1	3203.5	3172.1	3186.9
G11.0	3211.4	3216.8	3215.9	3211.9	3210.6	3204.5	3192.8	3182.1	3148.6	3164.9
G12.0	3192.3	3197.9	3195.8	3195.8	3189.8	3187.7	3169.2	3164.0	3119.5	3140.5
G13.0	3169.2	3177.1	3179.4	3172.1	3174.3	3166.1	3150.3	3143.6	3097.1	3117.8
G14.0	3143.3	3152.2	3153.0	3156.8	3150.2	3142.9	3121.1	3113.1	3065.7	3085.2
G15.0	3118.8	3130.7	3131.8	3136.2	3131.2	3120.0	3100.6	3083.0	3032.9	3054.6
G16.0	3092.8	3103.5	3107.9	3113.3	3105.7	3095.4	3075.0	3057.3	3003.3	3027.7
G17.0	3065.3	3070.1	3082.5	3087.2	3080.3	3071.5	3047.7	3028.1	2969.6	2994.1
G18.0	3032.4	3044.9	3049.9	3059.3	3058.8	3044.7	3020.6	2996.8	2931.3	2958.6
G19.0	3003.2	3011.6	3023.5	3032.9	3027.8	3013.4	2985.1	2961.9	2896.0	2928.4
G20.0	2968.0	2980.8	2992.4	3003.6	3000.8	2986.1	2955.9	2925.5	2858.2	2883.4
G21.0	2933.0	2942.8	2960.0	2970.2	2970.2	2960.3	2920.1	2891.0	2817.9	2850.6
G22.0	2896.2	2911.2	2923.6	2941.4	2940.3	2925.1	2887.6	2851.5	2779.5	2807.2
G23.0	2861.3	2871.4	2888.2	2904.7	2908.6	2890.0	2851.2	2811.8	2738.3	2766.7
G24.0	2818.5	2832.7	2856.2	2870.1	2875.3	2853.0	2814.0	2770.7	2694.0	2724.2
G25.0	2780.6	2792.4	2815.7	2837.8	2840.5	2818.0	2771.5	2728.8	2649.2	2686.0
G26.0	2740.8	2755.9	2778.5	2799.4	2803.9	2777.7	2730.5	2686.6	2604.2	2640.3
G27.0	2696.9	2712.9	2736.1	2763.7	2767.8	2741.7	2690.2	2646.3	2556.6	2594.5
G28.0	2654.5	2668.3	2698.1	2723.6	2730.4	2702.3	2649.7	2599.4	2510.7	2545.9
G29.0	2607.7	2621.4	2655.3	2682.4	2687.5	2660.5	2605.0	2552.5	2465.0	2498.8
G30.0	2560.2	2576.4	2610.7	2643.4	2645.3	2619.6	2561.4	2504.6	2416.0	2449.9
G31.0	2518.3	2532.5	2566.2	2598.9	2605.2	2575.2	2517.6	2460.0	2366.3	2402.5
G32.0	2468.9	2486.6	2521.3	2559.7	2562.5	2534.4	2469.8	2411.6	2315.8	2354.5
G33.0	2420.8	2437.5	2475.5	2514.4	2521.6	2486.9	2426.4	2364.1	2269.0	2302.4
G34.0	2373.7	2387.7	2426.6	2469.9	2476.6	2441.3	2376.5	2312.4	2217.5	2253.7
G35.0	2322.7	2341.5	2383.4	2422.2	2430.7	2399.8	2327.1	2265.2	2164.8	2205.9
G36.0	2274.0	2289.7	2332.4	2378.0	2385.6	2352.7	2279.1	2212.7	2113.0	2152.1

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G37.0	2224.2	2242.0	2288.3	2331.6	2338.9	2301.2	2229.6	2165.7	2063.8	2101.9
G38.0	2171.8	2193.2	2237.6	2283.1	2293.3	2255.7	2184.9	2114.9	2011.9	2050.3
G39.0	2120.8	2142.4	2187.1	2234.2	2245.9	2208.4	2133.2	2061.9	1959.1	2000.5
G40.0	2066.5	2085.8	2138.7	2188.0	2197.7	2160.9	2082.4	2011.1	1910.8	1950.8
G41.0	2017.8	2034.1	2087.2	2134.3	2145.3	2111.5	2029.0	1962.7	1859.7	1897.3
G42.0	1966.8	1984.9	2034.0	2085.9	2095.0	2060.3	1980.7	1912.0	1807.7	1843.2
G43.0	1916.5	1932.0	1985.9	2039.5	2048.9	2010.3	1930.1	1859.4	1755.5	1794.4
G44.0	1863.5	1884.5	1936.0	1984.6	2000.1	1961.2	1881.0	1806.7	1704.2	1742.6
G45.0	1811.3	1830.5	1883.0	1934.5	1948.0	1912.0	1828.7	1755.5	1654.4	1691.3
G46.0	1758.0	1781.2	1829.3	1883.4	1900.1	1857.4	1778.5	1706.2	1602.6	1638.9
G47.0	1707.2	1727.1	1782.1	1835.8	1846.5	1809.4	1728.1	1654.9	1552.4	1591.0
G48.0	1657.0	1678.1	1731.2	1784.7	1795.7	1757.6	1678.8	1605.1	1502.7	1540.3
G49.0	1605.3	1624.0	1675.2	1733.5	1746.9	1707.0	1625.7	1554.1	1454.4	1492.3
G50.0	1556.2	1575.8	1626.8	1681.7	1696.5	1652.9	1574.7	1504.7	1405.1	1440.8
G51.0	1506.0	1525.0	1579.6	1630.1	1646.0	1604.8	1525.8	1453.2	1357.0	1390.3
G52.0	1456.1	1475.1	1526.9	1579.7	1595.8	1553.3	1476.1	1406.0	1308.2	1342.9
G53.0	1408.1	1424.0	1473.8	1527.9	1543.5	1503.2	1426.5	1358.4	1261.2	1293.7
G54.0	1360.9	1375.1	1424.9	1479.4	1493.8	1454.2	1379.2	1311.4	1213.6	1246.8
G55.0	1311.0	1327.5	1379.8	1427.9	1443.5	1403.5	1327.2	1262.4	1166.8	1199.3
G56.0	1263.4	1279.0	1325.0	1379.0	1393.9	1353.5	1280.9	1214.2	1119.0	1153.1
G57.0	1215.0	1231.4	1278.9	1328.3	1341.1	1308.0	1231.8	1166.4	1074.3	1105.4
G58.0	1167.8	1182.0	1230.7	1279.9	1293.7	1255.6	1184.5	1120.6	1028.1	1060.5
G59.0	1121.8	1135.8	1182.3	1229.1	1242.7	1205.8	1135.6	1073.0	982.6	1015.1
G60.0	1077.6	1089.9	1134.2	1181.6	1194.0	1158.7	1088.4	1027.1	937.6	969.3
G61.0	1031.6	1043.1	1087.2	1133.5	1145.8	1110.5	1040.8	984.0	894.5	922.6
G62.0	984.6	998.7	1038.5	1084.6	1099.5	1062.0	997.7	939.1	852.1	878.0
G63.0	941.6	953.7	993.6	1037.9	1049.0	1015.4	952.0	894.2	809.8	836.5
G64.0	895.9	909.5	945.4	990.7	1000.7	968.9	905.1	850.2	767.1	792.7
G65.0	853.3	864.7	901.6	942.1	953.5	921.7	861.3	807.6	725.2	749.8
G66.0	812.3	819.6	855.9	897.7	908.0	877.7	816.4	764.2	688.3	708.7
G67.0	769.4	777.3	811.8	852.4	863.3	831.0	772.7	723.5	645.2	669.1
G68.0	725.9	735.8	769.1	804.6	815.6	784.6	728.9	687.6	604.4	628.4
G69.0	687.6	690.0	724.3	760.2	771.2	742.1	688.2	641.4	565.7	588.4
G70.0	645.5	653.8	688.7	716.7	727.7	698.1	646.8	602.0	526.9	549.4
G71.0	606.6	613.2	640.3	675.4	687.5	656.6	606.2	561.7	490.0	509.1
G72.0	567.5	573.6	600.2	630.5	639.4	613.1	564.5	523.8	453.0	470.7
G73.0	528.4	535.3	560.2	588.9	597.5	572.7	525.3	485.9	418.2	435.1

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G74.0	492.4	496.3	519.0	548.1	555.1	531.3	485.7	449.9	383.1	399.8
G75.0	454.3	458.7	480.6	508.1	513.7	492.1	447.6	412.1	345.0	363.1
G76.0	419.0	423.8	442.1	467.3	474.8	452.6	411.3	377.0	316.6	330.6
G77.0	383.8	387.9	405.5	428.9	435.4	413.9	374.3	342.7	282.7	296.3
G78.0	348.7	352.6	367.9	391.5	397.6	375.7	342.5	309.7	250.2	262.9
G79.0	317.5	319.2	334.4	353.2	358.5	342.6	303.4	275.9	219.9	232.4
G80.0	283.9	285.6	297.4	316.9	323.6	303.3	269.4	243.2	189.6	201.7
G81.0	252.4	252.7	264.0	282.3	286.5	268.6	235.4	213.6	161.0	170.2
G82.0	221.6	222.0	230.6	247.4	253.3	234.1	204.9	183.2	132.0	142.7
G83.0	191.8	191.3	199.4	213.7	219.6	201.2	171.7	153.9	106.7	114.0
G84.0	162.9	162.5	168.6	180.4	185.7	168.8	142.9	125.4	82.7	88.9
G85.0	135.6	133.9	137.8	148.5	154.1	136.2	112.1	98.7	60.7	65.5
G86.0	110.2	107.6	110.9	118.4	122.1	106.7	84.3	74.8	41.2	44.7
G87.0	83.4	82.5	82.9	88.9	92.5	76.7	59.9	51.5	22.7	25.7
G88.0	62.2	59.9	57.4	60.1	64.6	48.2	37.6	32.7	8.5	10.4
G89.0	42.5	39.8	36.2	35.1	37.5	24.8	18.3	15.9	3.1	3.6
G90.0	23.5	21.6	17.6	14.8	12.1	6.0	5.7	5.1	2.7	3.2
G91.0	9.9	8.2	5.4	3.2	3.6	3.5	3.8	3.7	3.0	3.2
G92.0	3.9	4.0	3.5	3.3	3.6	3.7	3.8	4.0	2.9	3.6
G93.0	3.6	4.0	3.6	3.5	3.7	3.8	4.0	3.7	3.1	3.3
G94.0	3.9	4.0	4.2	3.5	3.1	3.9	3.9	3.5	2.6	3.6
G95.0	4.0	4.2	3.9	4.0	4.0	4.3	3.9	3.7	3.6	3.6
G96.0	3.7	4.5	4.2	4.4	4.4	4.5	4.5	4.2	3.5	4.0
G97.0	4.0	4.6	4.4	4.4	4.9	4.8	3.9	4.2	3.5	3.7
G98.0	4.5	4.9	4.4	4.8	5.2	4.9	4.9	5.0	3.5	3.9
G99.0	4.9	5.1	4.9	4.6	5.1	5.1	4.6	4.8	4.0	4.6
G100.0	4.9	5.2	5.1	5.1	5.6	5.2	5.5	5.2	4.2	4.6
G101.0	5.0	5.6	5.4	5.2	5.6	5.8	5.1	5.1	4.4	4.4
G102.0	5.4	5.8	5.5	5.7	6.1	5.4	6.1	5.8	4.5	5.1
G103.0	5.2	4.9	5.5	6.0	6.3	6.1	6.1	6.1	4.8	5.0
G104.0	5.8	6.4	6.0	6.0	6.3	6.2	6.1	5.5	4.6	5.2
G105.0	5.8	6.3	6.0	5.7	6.5	6.7	6.7	5.7	5.2	5.8
G106.0	6.4	6.7	6.7	6.3	6.7	6.9	6.9	6.7	4.6	5.7
G107.0	6.4	7.0	6.8	7.1	7.5	7.4	7.1	7.0	5.7	6.0
G108.0	6.8	6.9	6.5	7.4	7.9	7.3	7.5	7.1	5.5	6.0
G109.0	7.0	7.6	7.1	7.5	8.1	7.6	7.7	7.6	6.3	6.7
G110.0	7.2	7.7	7.0	7.9	7.9	8.6	7.7	7.6	6.0	6.5

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 3)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G111.0	7.4	8.3	8.0	7.7	8.3	8.1	7.9	7.9	6.2	6.7
G112.0	7.2	8.3	8.0	8.4	9.2	8.6	8.3	8.3	6.5	7.1
G113.0	7.7	8.7	8.7	8.9	9.2	8.9	8.7	8.6	6.8	7.5
G114.0	8.0	8.7	8.8	8.9	9.3	9.4	9.2	8.8	7.1	8.0
G115.0	8.2	9.2	8.4	9.4	9.8	9.5	9.4	9.2	8.0	8.0
G116.0	9.0	9.4	8.9	9.0	10.0	9.5	9.6	8.8	7.0	8.4
G117.0	9.0	9.8	9.4	10.2	10.0	10.1	9.8	9.6	8.2	8.3
G118.0	9.0	10.1	9.2	10.1	10.5	10.1	10.1	9.9	7.5	8.7
G119.0	9.5	10.4	10.4	10.5	11.2	9.8	10.2	10.2	8.1	9.0
G120.0	9.7	10.2	10.7	10.4	11.3	11.1	10.6	10.5	8.8	9.2
G121.0	10.1	10.9	11.0	11.1	11.5	11.1	10.9	10.6	8.9	9.5
G122.0	10.3	11.2	11.0	11.3	12.1	11.4	11.5	10.9	9.4	9.9
G123.0	10.3	11.5	11.4	11.7	11.9	11.7	11.4	11.3	9.7	9.9
G124.0	11.2	12.2	11.8	12.1	12.4	12.3	11.5	11.3	10.0	10.4
G125.0	10.8	12.5	11.9	12.1	12.4	12.4	12.3	11.3	10.3	10.6
G126.0	11.4	12.0	12.0	12.5	13.0	12.6	12.5	12.4	10.1	10.8
G127.0	12.2	13.0	12.2	12.7	13.3	12.5	12.4	12.3	10.8	10.9
G128.0	12.5	13.1	12.6	13.3	13.4	13.6	12.7	12.6	11.2	11.5
G129.0	12.6	13.3	12.6	13.3	13.9	13.7	13.6	13.1	11.2	11.8
G130.0	12.8	13.5	13.5	13.6	13.9	14.3	13.7	13.2	11.5	11.7
G131.0	13.3	13.7	13.5	14.0	14.3	14.3	14.0	13.3	12.0	12.3
G132.0	13.3	14.4	13.8	14.5	14.7	14.4	14.4	13.8	11.6	12.4
G133.0	13.9	14.5	13.7	14.4	15.1	14.6	14.5	13.8	12.4	12.5
G134.0	14.4	14.9	14.9	14.8	15.2	14.8	14.9	14.5	12.6	13.5
G135.0	14.3	15.0	14.7	14.6	15.5	15.1	15.0	14.5	12.7	13.3
G136.0	14.6	15.0	15.1	15.4	15.7	15.7	15.1	15.5	13.3	14.1
G137.0	14.7	15.8	15.3	15.0	16.3	15.8	15.4	15.2	13.4	13.9
G138.0	14.9	15.7	15.7	16.1	16.3	16.4	15.8	15.2	13.5	13.8
G139.0	15.5	16.3	15.8	16.4	17.1	16.5	16.4	16.1	13.9	14.5
G140.0	15.5	16.8	16.1	16.3	17.2	16.7	16.2	16.2	14.3	15.1
G141.0	16.0	16.8	16.2	16.7	17.1	16.7	16.7	16.4	14.5	15.1
G142.0	16.0	17.3	16.1	17.1	17.5	17.1	16.5	16.5	15.0	15.3
G143.0	16.6	17.2	17.2	17.3	18.2	17.4	17.3	16.4	14.7	15.8
G144.0	16.8	17.4	17.0	17.6	17.6	17.5	17.3	17.5	15.7	16.4
G145.0	17.1	17.6	17.6	17.7	18.3	17.9	17.4	17.5	15.7	16.4
G146.0	17.5	18.0	18.0	18.1	18.5	18.1	17.7	18.0	15.9	16.7
G147.0	17.7	18.3	17.8	18.0	18.9	18.5	17.9	17.6	16.4	17.2

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 4)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G148.0	17.9	18.3	18.3	18.2	19.0	18.3	17.9	17.6	16.6	17.4
G149.0	18.2	18.9	18.3	18.3	19.3	18.9	18.8	18.4	16.9	17.3
G150.0	18.8	19.1	18.7	18.8	19.1	19.3	18.6	18.3	17.4	18.2
G151.0	18.5	19.3	19.1	19.4	19.4	19.7	18.8	18.9	17.5	18.1
G152.0	18.7	19.8	19.2	19.5	20.2	19.7	19.3	19.5	17.8	18.2
G153.0	19.1	20.1	19.5	19.5	20.2	19.3	19.8	19.6	18.1	18.8
G154.0	19.4	20.3	20.1	19.9	20.2	19.7	19.9	20.0	18.1	18.7
G155.0	19.7	20.6	20.4	20.3	20.6	20.3	19.8	20.2	18.5	19.4
G156.0	19.9	20.6	20.1	20.9	20.7	21.0	20.5	20.3	18.7	19.2
G157.0	19.7	21.0	20.5	20.9	20.6	20.6	20.3	20.5	19.3	19.7
G158.0	20.2	21.0	21.0	20.5	21.4	21.2	20.7	20.6	19.4	20.1
G159.0	20.7	21.3	21.3	21.1	21.4	20.7	20.7	20.7	19.5	20.5
G160.0	21.0	21.3	21.1	20.7	21.3	21.1	21.2	20.7	19.7	21.0
G161.0	21.4	21.8	21.6	21.4	21.8	21.7	20.9	21.2	20.1	20.8
G162.0	21.2	21.9	21.4	21.4	21.6	21.4	21.5	21.3	20.8	21.0
G163.0	21.9	21.7	21.2	21.4	21.9	21.6	21.5	22.0	20.3	21.4
G164.0	21.7	22.7	21.7	21.8	22.2	21.9	21.8	21.7	20.8	21.8
G165.0	22.5	22.5	21.9	21.9	22.5	22.0	21.9	22.1	21.0	21.6
G166.0	21.9	22.6	22.0	22.7	22.2	22.5	21.9	22.4	21.5	21.7
G167.0	22.3	22.9	22.4	22.5	22.6	22.3	22.1	22.5	21.4	22.4
G168.0	23.2	22.5	23.1	22.8	22.5	22.9	22.0	22.6	21.5	22.2
G169.0	23.0	23.2	22.5	23.0	22.6	22.9	22.8	23.3	22.2	22.4
G170.0	23.2	23.8	22.6	23.2	22.6	22.9	22.5	23.1	21.9	22.9
G171.0	22.7	23.5	22.6	23.1	23.1	23.3	22.6	23.1	22.8	22.9
G172.0	22.8	23.3	23.3	23.4	23.1	22.9	23.0	22.7	22.9	23.5
G173.0	23.2	23.9	23.5	23.3	22.8	23.0	22.8	23.0	22.7	23.3
G174.0	23.5	23.3	23.3	23.7	23.1	22.6	23.3	23.4	22.8	23.3
G175.0	23.3	24.1	23.3	23.8	23.7	23.3	23.3	23.1	23.2	23.9
G176.0	24.0	24.4	23.5	23.0	23.8	23.0	23.2	23.3	23.8	23.8
G177.0	23.8	24.1	23.3	23.6	23.2	23.2	23.4	23.4	23.5	23.8
G178.0	23.8	24.1	23.7	23.2	23.7	23.6	23.6	23.6	23.8	23.9
G179.0	23.9	24.2	23.3	23.6	23.8	23.3	23.6	23.6	23.9	24.2
G180.0	24.2	24.4	23.9	23.3	23.5	23.5	23.1	23.6	23.8	24.8

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 5)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G0.0	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5	3301.5			
G1.0	3301.0	3297.2	3298.4	3302.2	3298.2	3299.8	3304.6			
G2.0	3295.7	3291.4	3295.9	3296.5	3299.7	3294.8	3306.0			
G3.0	3286.3	3285.2	3287.9	3297.3	3292.4	3294.4	3302.9			
G4.0	3281.0	3283.0	3282.7	3290.3	3289.1	3285.6	3297.3			
G5.0	3270.7	3270.7	3276.7	3285.6	3279.2	3277.3	3296.1			
G6.0	3255.8	3265.2	3264.7	3273.7	3272.3	3267.8	3284.7			
G7.0	3245.7	3252.2	3253.1	3256.0	3258.9	3253.6	3274.1			
G8.0	3230.7	3238.4	3242.5	3252.6	3246.7	3241.7	3260.2			
G9.0	3215.7	3227.0	3228.5	3234.1	3234.1	3227.3	3247.9			
G10.0	3194.1	3204.5	3214.6	3221.1	3222.2	3205.9	3229.5			
G11.0	3175.7	3186.9	3197.1	3206.5	3198.6	3188.5	3211.4			
G12.0	3154.0	3166.4	3178.8	3190.1	3177.7	3168.3	3192.3			
G13.0	3129.9	3143.9	3158.1	3164.4	3156.6	3144.8	3169.2			
G14.0	3104.3	3123.5	3139.5	3145.0	3134.0	3121.5	3143.3			
G15.0	3078.0	3102.9	3115.0	3123.6	3107.4	3096.8	3118.8			
G16.0	3049.6	3077.4	3095.2	3094.3	3080.4	3065.6	3092.8			
G17.0	3022.9	3048.7	3067.1	3065.2	3053.6	3036.6	3065.3			
G18.0	2987.3	3018.7	3039.0	3046.1	3023.6	3002.4	3032.4			
G19.0	2959.4	2989.0	3013.6	3015.9	2990.7	2971.3	3003.2			
G20.0	2924.2	2955.4	2983.1	2984.5	2962.3	2933.9	2968.0			
G21.0	2885.6	2927.9	2952.1	2952.8	2929.3	2899.0	2933.0			
G22.0	2848.5	2893.7	2916.3	2921.0	2896.4	2863.4	2896.2			
G23.0	2811.0	2858.5	2885.0	2884.1	2857.7	2824.9	2861.3			
G24.0	2770.6	2818.1	2850.5	2847.7	2818.6	2788.3	2818.5			
G25.0	2732.6	2781.4	2812.8	2813.0	2779.5	2745.9	2780.6			
G26.0	2687.1	2742.5	2778.7	2775.3	2743.4	2703.2	2740.8			
G27.0	2648.4	2706.0	2736.3	2738.5	2699.9	2659.0	2696.9			
G28.0	2600.7	2665.6	2702.1	2696.6	2659.8	2617.6	2654.5			
G29.0	2557.7	2625.2	2657.6	2656.8	2615.7	2568.9	2607.7			
G30.0	2510.6	2579.2	2619.0	2614.0	2572.8	2525.6	2560.2			
G31.0	2469.8	2534.0	2573.8	2573.6	2529.9	2477.1	2518.3			
G32.0	2421.1	2487.3	2530.5	2528.7	2481.4	2429.9	2468.9			
G33.0	2372.4	2445.8	2487.8	2482.1	2435.2	2381.8	2420.8			
G34.0	2323.4	2397.9	2440.8	2437.3	2390.6	2329.7	2373.7			
G35.0	2274.2	2354.0	2396.0	2391.9	2341.5	2280.4	2322.7			
G36.0	2226.7	2303.6	2350.0	2341.9	2294.4	2229.1	2274.0			

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 6)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G37.0	2173.8	2257.0	2301.7	2292.7	2244.9	2181.8	2224.2			
G38.0	2124.8	2205.9	2257.8	2247.9	2193.8	2130.8	2171.8			
G39.0	2074.5	2159.1	2210.1	2198.3	2145.1	2076.4	2120.8			
G40.0	2022.0	2108.1	2157.3	2149.0	2092.9	2029.5	2066.5			
G41.0	1973.4	2059.1	2108.0	2100.4	2042.3	1975.7	2017.8			
G42.0	1923.1	2009.7	2057.7	2051.3	1990.6	1924.9	1966.8			
G43.0	1872.1	1959.3	2006.7	2000.6	1940.3	1872.7	1916.5			
G44.0	1821.4	1905.5	1959.0	1947.5	1887.6	1821.8	1863.5			
G45.0	1771.4	1855.5	1905.9	1898.8	1838.4	1769.2	1811.3			
G46.0	1718.3	1804.1	1857.3	1844.5	1780.8	1717.4	1758.0			
G47.0	1666.2	1752.2	1806.9	1795.8	1735.2	1668.2	1707.2			
G48.0	1616.2	1702.8	1755.4	1743.3	1683.8	1615.8	1657.0			
G49.0	1565.1	1650.7	1702.7	1694.0	1630.1	1563.3	1605.3			
G50.0	1516.2	1601.8	1654.7	1641.6	1582.0	1516.2	1556.2			
G51.0	1465.7	1550.5	1599.5	1592.7	1530.5	1466.2	1506.0			
G52.0	1416.2	1498.2	1547.6	1541.4	1478.7	1416.6	1456.1			
G53.0	1367.3	1448.9	1498.9	1489.1	1429.9	1366.9	1408.1			
G54.0	1318.1	1402.2	1447.3	1438.3	1381.1	1318.3	1360.9			
G55.0	1271.4	1348.2	1397.3	1387.0	1330.1	1270.5	1311.0			
G56.0	1220.0	1298.6	1344.6	1339.2	1281.3	1221.7	1263.4			
G57.0	1171.8	1247.4	1297.7	1287.5	1232.7	1173.5	1215.0			
G58.0	1125.1	1199.7	1248.2	1236.4	1186.2	1127.3	1167.8			
G59.0	1077.3	1151.0	1195.5	1188.6	1134.9	1080.2	1121.8			
G60.0	1032.5	1101.6	1148.5	1139.5	1090.4	1035.4	1077.6			
G61.0	985.7	1056.7	1098.6	1093.2	1040.5	989.3	1031.6			
G62.0	940.1	1007.8	1049.4	1044.6	993.7	944.3	984.6			
G63.0	893.0	962.6	1003.1	997.5	947.2	900.4	941.6			
G64.0	848.9	918.2	956.6	949.9	901.9	855.9	895.9			
G65.0	804.3	870.6	907.2	902.1	857.7	812.7	853.3			
G66.0	760.8	822.3	862.8	855.4	813.8	768.4	812.3			
G67.0	717.0	779.3	816.3	808.2	768.7	728.1	769.4			
G68.0	678.0	733.9	767.8	765.4	723.9	689.1	725.9			
G69.0	634.3	689.0	724.2	720.0	688.8	645.0	687.6			
G70.0	593.7	648.2	685.1	679.8	641.7	604.7	645.5			
G71.0	553.2	606.0	638.6	633.9	597.9	565.6	606.6			
G72.0	513.9	563.3	595.0	590.9	558.3	526.9	567.5			
G73.0	475.9	525.0	553.4	551.5	519.6	489.6	528.4			

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 7)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G74.0	435.7	482.4	513.5	508.5	480.6	452.7	492.4			
G75.0	398.4	444.4	471.6	470.2	442.0	415.2	454.3			
G76.0	361.9	406.5	433.0	431.2	404.2	380.2	419.0			
G77.0	328.8	368.8	394.7	391.4	367.4	343.4	383.8			
G78.0	293.2	332.7	355.2	353.9	331.8	311.8	348.7			
G79.0	259.1	295.4	319.5	317.8	298.6	277.7	317.5			
G80.0	226.5	260.0	283.6	282.0	264.0	245.5	283.9			
G81.0	194.2	225.6	248.3	247.3	228.3	214.4	252.4			
G82.0	162.6	192.4	214.2	212.4	197.7	183.9	221.6			
G83.0	133.3	161.6	182.0	180.0	165.9	155.8	191.8			
G84.0	103.0	128.5	150.1	148.1	135.9	127.5	162.9			
G85.0	77.3	100.1	119.0	117.0	107.1	100.7	135.6			
G86.0	52.3	71.4	89.9	87.0	79.6	76.1	110.2			
G87.0	32.1	44.0	60.8	58.5	54.1	53.7	83.4			
G88.0	13.7	21.4	32.3	32.6	33.3	34.2	62.2			
G89.0	3.7	5.5	8.3	12.6	14.9	16.4	42.5			
G90.0	2.4	2.0	2.3	2.3	3.7	4.9	23.5			
G91.0	2.6	2.6	2.7	2.5	2.7	2.6	9.9			
G92.0	2.9	2.9	2.7	2.5	2.6	2.7	3.9			
G93.0	2.7	2.7	2.7	2.9	3.1	2.7	3.6			
G94.0	3.1	2.9	2.9	3.0	2.5	3.2	3.9			
G95.0	3.6	3.2	2.9	3.0	3.1	3.2	4.0			
G96.0	2.9	3.7	3.2	2.7	3.2	3.3	3.7			
G97.0	3.6	3.7	3.6	3.0	3.5	3.6	4.0			
G98.0	3.9	3.9	3.7	3.8	3.8	3.3	4.5			
G99.0	3.8	4.0	3.9	3.7	3.5	3.5	4.9			
G100.0	3.8	3.5	3.9	3.9	4.2	4.0	4.9			
G101.0	4.2	4.6	4.2	4.5	3.5	3.9	5.0			
G102.0	4.8	4.5	4.8	4.4	4.4	4.5	5.4			
G103.0	4.6	4.8	5.1	3.9	4.6	4.5	5.2			
G104.0	4.6	5.0	5.0	4.6	4.9	4.9	5.8			
G105.0	5.2	5.4	5.5	5.5	4.9	4.8	5.8			
G106.0	5.4	5.4	5.8	5.7	5.0	4.8	6.4			
G107.0	5.1	6.0	6.0	5.5	5.2	5.0	6.4			
G108.0	5.8	6.2	6.3	5.6	5.5	5.5	6.8			
G109.0	6.3	6.3	6.3	5.7	6.2	6.0	7.0			
G110.0	6.0	6.5	6.9	6.4	6.0	5.6	7.2			

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 8)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G111.0	6.7	6.7	7.0	6.8	6.4	6.3	7.4			
G112.0	6.5	6.9	7.3	7.0	6.4	6.7	7.2			
G113.0	7.1	7.3	7.3	7.3	6.9	6.7	7.7			
G114.0	7.5	7.7	7.7	7.7	7.0	6.9	8.0			
G115.0	7.3	7.6	8.2	7.9	7.1	6.9	8.2			
G116.0	7.9	8.0	8.1	8.3	7.9	7.5	9.0			
G117.0	7.9	8.7	8.3	8.4	7.6	7.6	9.0			
G118.0	8.4	8.3	8.9	7.9	7.9	8.0	9.0			
G119.0	8.3	8.7	9.0	9.0	8.6	8.7	9.5			
G120.0	8.9	9.0	9.8	9.0	8.7	7.7	9.7			
G121.0	9.0	8.4	9.4	9.3	8.4	8.7	10.1			
G122.0	9.3	9.6	9.9	9.6	9.0	9.3	10.3			
G123.0	9.9	10.0	9.9	9.0	9.4	9.4	10.3			
G124.0	10.1	10.1	10.8	10.5	10.1	9.6	11.2			
G125.0	9.8	10.4	10.9	10.7	10.1	9.5	10.8			
G126.0	10.7	10.8	11.3	10.5	10.0	9.8	11.4			
G127.0	11.0	11.1	11.2	10.9	10.7	10.1	12.2			
G128.0	11.2	11.1	11.7	11.5	10.9	10.7	12.5			
G129.0	11.1	11.7	12.4	11.9	10.9	11.3	12.6			
G130.0	11.9	12.0	12.1	11.1	11.7	10.9	12.8			
G131.0	12.4	12.0	12.4	12.0	11.8	11.3	13.3			
G132.0	12.5	12.5	12.9	12.5	12.3	11.5	13.3			
G133.0	12.5	12.5	13.1	12.5	12.4	12.3	13.9			
G134.0	12.8	13.1	13.6	12.9	12.6	13.0	14.4			
G135.0	12.9	13.6	13.9	13.4	13.2	12.9	14.3			
G136.0	13.7	14.2	14.0	13.6	13.3	13.0	14.6			
G137.0	13.8	14.2	14.3	14.2	13.4	13.1	14.7			
G138.0	14.2	14.3	14.7	14.2	14.3	13.8	14.9			
G139.0	14.4	14.5	14.7	14.6	14.0	14.0	15.5			
G140.0	13.9	15.0	15.6	14.2	14.4	14.0	15.5			
G141.0	14.9	15.6	15.7	15.0	14.6	14.0	16.0			
G142.0	15.5	15.1	16.2	15.6	14.8	14.6	16.0			
G143.0	15.3	15.8	16.2	15.9	15.1	15.1	16.6			
G144.0	15.6	16.1	16.3	16.1	15.8	15.1	16.8			
G145.0	16.2	16.5	16.5	16.3	16.1	15.9	17.1			
G146.0	16.4	17.1	16.9	16.8	16.1	15.7	17.5			
G147.0	16.3	16.9	17.5	16.7	16.3	16.5	17.7			

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector:

Candlepower Table (Continue 9)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G148.0	16.9	16.8	17.5	17.3	16.4	16.3	17.9			
G149.0	17.3	17.5	17.8	17.4	17.1	16.8	18.2			
G150.0	17.5	17.5	18.2	18.3	17.3	17.0	18.8			
G151.0	17.9	17.9	18.7	17.6	17.4	17.9	18.5			
G152.0	18.2	18.0	18.3	18.7	17.7	17.3	18.7			
G153.0	18.0	18.7	18.7	18.3	18.4	18.0	19.1			
G154.0	18.1	18.7	19.0	18.7	18.4	18.2	19.4			
G155.0	18.9	19.4	19.4	18.6	18.2	18.1	19.7			
G156.0	19.2	19.5	19.9	19.9	19.3	18.4	19.9			
G157.0	19.2	19.8	19.9	19.7	19.2	19.2	19.7			
G158.0	19.9	19.6	20.0	19.7	19.6	18.9	20.2			
G159.0	19.7	20.1	20.1	20.5	19.6	19.5	20.7			
G160.0	20.0	20.2	20.4	20.3	19.6	19.3	21.0			
G161.0	19.5	20.8	20.7	20.5	20.0	19.4	21.4			
G162.0	20.4	20.2	20.9	21.1	20.7	20.1	21.2			
G163.0	20.7	20.7	21.4	20.8	20.3	20.1	21.9			
G164.0	21.3	20.8	21.5	21.1	20.9	20.7	21.7			
G165.0	21.4	21.2	21.4	21.6	21.2	20.9	22.5			
G166.0	21.4	21.7	21.8	21.6	21.3	20.7	21.9			
G167.0	22.0	21.5	22.0	21.8	21.5	21.7	22.3			
G168.0	21.8	22.1	22.0	21.9	21.8	21.9	23.2			
G169.0	22.2	22.4	22.2	22.2	22.0	21.8	23.0			
G170.0	21.7	22.0	22.5	22.4	22.0	22.0	23.2			
G171.0	22.5	22.8	22.4	22.4	22.6	22.4	22.7			
G172.0	22.9	22.3	22.8	22.6	22.1	22.8	22.8			
G173.0	22.7	22.8	22.7	22.6	22.6	22.8	23.2			
G174.0	22.6	22.8	22.9	22.6	22.7	22.8	23.5			
G175.0	22.9	23.2	22.8	22.9	22.8	23.2	23.3			
G176.0	23.2	23.6	23.3	23.3	23.4	23.3	24.0			
G177.0	23.2	23.4	23.5	23.1	23.3	23.6	23.8			
G178.0	23.2	23.3	22.9	23.1	23.4	23.1	23.8			
G179.0	23.1	23.8	23.4	23.1	23.6	23.7	23.9			
G180.0	23.2	24.0	24.1	23.0	23.3	23.7	24.2			

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 8.190 m
Humidity:
Inspector: